



AISIN Fully Synthetic Motor Oil

PREMIUM PERFORMANCE DIESEL ENGINE OIL

Premium performance, multigrade, heavy-duty diesel engine oil specifically designed to lubricate a wide range of diesel and gasoline engines requiring API CI-4, SJ, ACEA E7 performance lubricants operating under the most severe service conditions.

APPLICATIONS

- Mixed fleets of European, North American diesel engines (high speed, four-stroke, turbocharged or naturally aspirated)
- Mixed fleets of both diesel and gasoline engines
- Mixed fleets including both old and new equipment
- Commercial road transport, including the latest electronic controlled engines.
- Stop-and-go vehicles in high soot loading service such as buses and waste collection trucks
- Off-highway vehicles and plant

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended. Aisin, the Aisin logo and related marks are trademarks of Aisin Asia Pte Ltd, used under licence.

PERFORMANCE STANDARDS

- API CI-4, CH-4, CG-4, CF-4
- API SJ
- ACEA E7
- Volvo VDS-3
- Mercedes-Benz 228.3

BENEFITS

- **Minimizes fleet maintenance costs**

Exceptional soot dispersancy keeps fuel soot in suspension, avoiding filter plugging, cylinder head sludge, abrasive polishing wear and oil thickening.

- **Minimizes fleet operating costs**

Excellent deposit control on valves and piston crownlands reduces oil consumption. Exceptional oxidation stability and soot control extends oil drain capability so that equipment is in service longer generating revenue. Outstanding valve train wear protection maintains fuel economy.

- **Extends engine life to overhaul**

High level of anti-wear additive protects against valve train wear and scuffing of highly loaded parts operating under boundary lubrication conditions.

KEY PROPERTIES

SAE Viscosity	Base Number (D2896, mg KOH/g)	Kinematic Viscosity, mm ² /s		Viscosity Index	Pour Point (°C)	Flash Point (°C)
		@ 40°C	@ 100°C			
10W-40	9.5	105.1	15.5	156	-33	220

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended. Aisin, the Aisin logo and related marks are trademarks of Aisin Asia Pte Ltd, used under licence.